


Style O15A1

Flange Adaptor Class150

Publication: 01.12.04EN




Nominal Size	OD	EE	D	N-L	Approx. Wt. Ea.
Inches mm	Inches mm	Inches mm	Inches mm	Inches mm	Lbs. kg
1¼	1.660	2.36	3.50	4-Φ0.63	2.9
32	42.4	60	88.9	4-Φ16	1.3
1½	1.900	2.36	3.87	4-Φ0.63	3.7
40	48.3	60	98.4	4-Φ16	1.7
2	2.375	2.76	4.75	4-Φ0.75	3.7
50	60.3	70	120.7	4-Φ19	1.7
2½	2.875	2.76	5.50	4-Φ0.75	9.3
65	73.0	70	139.7	4-Φ19	4.2
3	3.500	2.76	6.00	4-Φ0.75	10.8
80	88.9	70	152.4	4-Φ19	4.9
4	4.500	3.15	7.50	8-Φ0.75	13.9
100	114.3	80	190.5	8-Φ19	6.3
5	5.563	3.15	8.50	8-Φ0.91	17.0
125	141.3	80	215.9	8-Φ23	7.7
6	6.625	3.94	9.5	8-Φ0.91	21.2
150	168.3	100	241.3	8-Φ23	9.6
8	8.625	3.94	11.75	8-Φ0.91	26.5
200	219.1	100	298.5	8-Φ23	12.0
10	10.750	3.94	14.25	12-Φ1.02	41.4
250	273.0	100	362	12-Φ26	18.8
12	12.750	3.94	17.00	12-Φ1.02	57.5
300	323.9	100	431.8	12-Φ26	26.1

Style O15A2

Flange Adaptor Class300

Publication: 01.12.04EN




Nominal Size	OD	EE	D	N-L	Approx. Wt. Ea.
Inches Mm	Inches mm	Inches mm	Inches mm	Inches mm	Lbs. kg
1¼	1.660	2.36	3.87	4-Φ0.75	4.8
32	42.4	60	98.4	4-Φ19	2.2
1½	1.900	2.36	4.50	4-Φ0.91	7.0
40	48.3	60	114.3	4-Φ23	3.2
2	2.375	2.76	5.00	8-Φ0.75	7.9
50	60.3	70	127.0	8-Φ19	3.6
2½	2.875	2.76	5.87	8-Φ0.91	11.2
65	73.0	70	149.2	8-Φ23	5.1
3	3.500	2.76	6.63	8-Φ0.91	14.8
80	88.9	70	168.3	8-Φ23	6.7
4	4.500	3.15	7.87	8-Φ0.91	18.9
100	114.3	80	200.0	8-Φ23	8.6
5	5.563	3.15	9.25	8-Φ0.91	27.5
125	141.3	80	235.0	8-Φ23	12.5
6	6.625	3.94	10.63	12-Φ0.91	35.2
150	168.3	100	269.9	12-Φ23	16.0
8	8.625	3.94	13.00	12-Φ1.02	45.4
200	219.1	100	330.2	12-Φ26	20.6
10	10.750	3.94	15.25	16-Φ1.14	69.4
250	273.0	100	387.4	16-Φ29	31.5
12	12.750	3.94	17.75	16-Φ1.26	94.5
300	323.9	100	450.8	16-Φ32	42.9

Style O15D2

Flange Adaptor PN16

Publication: 01.12.03EN



Nominal Size	OD	EE	D	N-L	Approx. Wt. Ea.
Inches mm	Inches mm	Inches mm	Inches mm	Inches mm	Lbs. kg
2	2.375	2.76	4.92	4-Φ0.71	3.7
50	60.3	70	125	4-Φ18	1.7
3OD	3.000	2.76	5.71	8-Φ0.71	5.3
65	76.1	70	145	8-Φ18	2.4
3	3.500	2.76	6.3	8-Φ0.71	5.9
80	88.9	70	160	8-Φ18	2.7
4	4.500	3.15	7.09	8-Φ0.71	7.5
100	114.3	80	180	8-Φ18	3.4
5½OD	5.500	3.15	8.27	8-Φ0.71	9.3
125	139.7	80	210	8-Φ18	4.2
6½OD	6.500	3.94	9.45	8-Φ0.91	12.8
150	165.1	100	240	8-Φ23	5.8
6	6.625	3.94	9.45	8-Φ0.91	12.8
150	168.3	100	240	8-Φ23	5.8
8	8.625	3.94	11.61	12-Φ0.91	19.4
200	219.1	100	295	12-Φ23	8.8
10	10.750	3.94	13.98	12-Φ0.98	27.8
250	273.0	100	355	12-Φ25	12.6
12	12.750	3.94	16.14	12-Φ0.98	32.8
300	323.9	100	410	12-Φ25	14.9

- UL Listed and FM Approved pressure rate is the same as Style 001 Coupling.
- A1: Class 125 or Class 150, A2: Class 300, D2: 16bar.
- All Flange Adaptor designed to mate with raised-face flanges, but can supply with flat-face.
- For correct installation, please refer to Page 91 "General of installation" and Publication AZ-100-EN "Installation Manual"
- FOR ONE TIME FIELD TEST ONLY, the Max. Joint Working Pressure may be increased to 1.5 times the figures shown.

Australia Standard-Table E

Nominal Size	OD	EE	D	N-L	Approx. Wt. Ea.
Inches mm	Inches mm	Inches mm	Inches mm	Inches mm	Lbs. kg
2	2.375	2.76	4.49	4-Φ0.71	3.5
50	60.3	70	114	4-Φ18	1.6
3OD	3.000	2.76	5.00	4-Φ0.71	5.1
65	76.1	70	127	4-Φ18	2.3
3	3.500	2.76	5.75	4-Φ0.71	5.7
80	88.9	70	146	4-Φ18	2.6
4	4.500	3.15	7.01	8-Φ0.71	7.0
100	114.3	80	178	8-Φ18	3.2
5½OD	5.500	3.15	8.27	8-Φ0.71	8.8
125	139.7	80	210	8-Φ18	4.0
6½OD	6.500	3.94	9.25	8-Φ0.87	12.1
150	165.1	100	235	8-Φ22	5.5
6	6.625	3.94	9.25	8-Φ0.87	12.1
150	168.3	100	235	8-Φ22	5.5
8	8.625	3.94	11.50	8-Φ0.87	18.5
200	219.1	100	292	8-Φ22	8.4
10	10.750	3.94	14.02	12-Φ0.87	26.4
250	273.0	100	356	12-Φ22	12.0
12	12.750	3.94	15.98	12-Φ1.02	31.3
300	323.9	100	406	12-Φ26	14.2

