


### Style 008

#### Concentric Reducer (G)

Publication: 01.11.01EN




OD	EE	Approx. Wt. Ea.
Inches	Inches	Lbs.
Mm	mm	kg
2x1½	2.52	0.7
60.3x42.4	64	0.3
2x1½	2.52	0.7
60.3x48.3	64	0.3
2½x1½	2.52	0.9
73.0x42.4	64	0.4
2½x1½	2.52	0.9
73.0x48.3	64	0.4
2½x2	2.52	1.1
73.0x60.3	64	0.5
3ODx1½	2.52	0.9
76.1x42.4	64	0.4
3ODx1½	2.52	0.9
76.1x48.3	64	0.4
3ODx2	2.52	1.1
76.1x60.3	64	0.5
3x1½	2.52	0.9
88.9x42.4	64	0.4
3x1½	2.52	0.9
88.9x48.3	64	0.4
3x2	2.52	1.1
88.9x60.3	64	0.5
3x2½	2.52	1.3
88.9x73.0	64	0.6
3x3OD	2.52	1.3
88.9x76.1	64	0.6
4x1½	2.99	2.2
114.3x42.4	76	1.0
4x1½	2.99	2.4
114.3x48.3	76	1.1
4x2	2.99	2.4
114.3x60.3	76	1.1
4x2½	2.99	2.6
114.3x73.0	76	1.2
4x3OD	2.99	2.6
114.3x76.1	76	1.2
4x3	2.99	3.1
114.3x88.9	76	1.4

### Style 008 CONT'D

#### Concentric Reducer (G)

Publication: 01.11.01EN




OD	EE	Approx. Wt. Ea.
Inches	Inches	Lbs.
Mm	mm	kg
5½ODx2	7.76	7.7
139.7x60.3	197 #	3.5
5½ODx3OD	7.76	8.4
139.7x76.1	197 #	3.8
5½ODx3	7.76	9
139.7x88.9	197 #	4.1
5½ODx4	3.50	3.7
139.7x114.3	89	1.7
5x2	7.76	7.7
141.3x60.3	197 #	3.5
5x2½	7.76	8.6
141.3x73.0	197 #	3.9
5x3	7.76	9.3
141.3x88.9	197 #	4.2
5x4	3.50	3.7
141.3x114.3	89	1.7
6½ODx2	4.02	4.8
165.1x60.3	102	2.2
6½ODx3OD	4.02	5.1
165.1x76.1	102	2.3
6½ODx3	4.02	5.7
165.1x88.9	102	2.6
6½ODx4	4.02	6.2
165.1x114.3	102	2.8
6½ODx5½OD	4.02	6.4
165.1x139.7	102	2.9
6x2	4.02	4.8
168.3x60.3	102	2.2
6x2½	4.02	4.8
168.3x73.0	102	2.2
6x3OD	4.02	5.1
168.3x76.1	102	2.3
6x3	4.02	5.7
168.3x88.9	102	2.6
6x4	4.02	6.2
168.3x114.3	102	2.8
6x5½OD	8.27	14.3
168.3x139.7	210 #	6.5

### Style 008 CONT'D

#### Concentric Reducer (G)

Publication: 01.11.01EN



OD	EE	Approx. Wt. Ea.
Inches	Inches	Lbs.
Mm	mm	kg
8x2	5.00	10.1
219.1x60.3	127	4.6
8x3OD	5.00	10.4
219.1x76.1	127	4.7
8x3	5.00	10.6
219.1x88.9	127	4.8
8x4	5.00	10.8
219.1x114.3	127	4.9
8x5½OD	5.00	11.2
219.1x139.7	127	5.1
8x6½OD	5.00	11.5
219.1x165.1	127	5.2
8x6	5.00	11.5
219.1x168.3	127	5.2
10x4	10.35	23.3
273.0x114.3	263 #	10.6
10x5½OD	10.35	24.7
273.0x139.7	263 #	11.2
10x5	10.35	24.9
273.0x141.3	263 #	11.3
10x6½OD	10.35	26.4
273.0x165.1	263 #	12.0
10x6	10.35	26.4
273.0x168.3	263 #	12.0
10x8	10.35	30.3
273.0x219.1	263 #	13.7
12x4	11.34	30.6
323.9x114.3	288 #	13.9
12x5	11.34	32.4
323.9x141.3	288 #	14.7
12x6½OD	11.34	34.0
323.9x165.1	288 #	15.5
12x6	11.34	34.0
323.9x168.3	288 #	15.5
12x8	11.93	39.7
323.9x219.1	303 #	18.0
12x10	11.93	46.4
323.9x273.0	303 #	21.1

- UL Listed and FM Approved pressure rate is the same as Style 101H Coupling, for more details refer to page 17.
- For more size ,please refer to "General catalog"
- For correct installation ,please refer to Page 91"General of installation" and Publication AZ-100-EN"Installation Manual"
- FOR ONE TIME FIELD TEST ONLY, the Max. Joint Working Pressure may be increased to 1.5 times the figures shown.

# Segmentally Welded Steel.  
LPC refer to page 13 for details.

