


## Style 002

### Short Pattern 90° Elbow

Publication: 01.09.01EN




Nominal Size	OD	CE	Approx. Wt. Ea.
Inches mm	Inches mm	Inches mm	Lbs. kg
2	2.375	2.76	1.5
50	60.3	70	0.7
2½	2.875	2.99	2.4
65	73.0	76	1.1
3OD	3.000	2.99	2.4
65	76.1	76	1.1
3	3.500	3.39	2.6
80	88.9	86	1.2
4	4.500	4.02	4.8
100	114.3	102	2.2
5½OD	5.500	4.88	7.9
125	139.7	124	3.6
5	5.563	4.88	7.9
125	141.3	124	3.6
6½OD	6.500	5.51	11.5
150	165.1	140	5.2
6	6.625	5.51	11.7
150	168.3	140	5.3
8	8.515	6.81	20.0
200A %	216.3	173	9.1
8	8.625	6.81	20.0
200	219.1	173	9.1

## Style 004

### Short Pattern Equal Tee

Publication: 01.09.03EN




Nominal Size	OD	CE	Approx. Wt. Ea.
Inches mm	Inches mm	Inches mm	Lbs. kg
2	2.375	2.76	2.2
50	60.3	70	1.0
2½	2.875	2.99	3.1
65	73.0	76	1.4
3OD	3.000	2.99	3.1
65	76.1	76	1.4
3	3.500	3.39	4.0
80	88.9	86	1.8
4	4.500	4.02	6.8
100	114.3	102	3.1
5½OD	5.500	4.88	10.6
125	139.7	124	4.8
5	5.563	4.88	10.6
125	141.3	124	4.8
6½OD	6.500	5.51	15.4
150	165.1	140	7.0
6	6.625	5.51	15.9
150	168.3	140	7.2
8	8.515	6.81	30.0
200A %	216.3	173	13.6
8	8.625	6.81	30.0
200	219.1	173	13.6

## Style 010

### Short Pattern Equal Cross

Publication: 01.09.05EN



Nominal Size	OD	CE	Approx. Wt. Ea.
Inches mm	Inches mm	Inches mm	Lbs. kg
2	2.375	2.76	2.9
50	60.3	70	1.3
2½	2.875	2.99	4.2
65	73.0	76	1.9
3OD	3.000	2.99	4.4
65	76.1	76	2.0
3	3.500	3.39	5.3
80	88.9	86	2.4
4	4.500	4.02	8.1
100	114.3	102	3.7
5½OD	5.500	4.88	12.3
125	139.7	124	5.6
5	5.563	4.88	12.3
125	141.3	124	5.6
6½OD	6.500	5.51	17.8
150	165.1	140	8.1
6	6.625	5.51	18.1
150	168.3	140	8.2
8	8.515	6.81	37.9
200A %	216.3	173	17.2
8	8.625	6.81	37.9
200	219.1	173	17.2

- Style 002, 004, 010 are short pattern design, Equivalent length please refer to page24.
- UL Listed and FM Approved pressure rate of Style 002, 004 and 010 are the same as Style 001coupling, please refer to page 15.
- For Style 003 standard 45°Elbow, Please refer to page 27. For Style 005 end cap, please refer to page 28.
- Less than 2", Style 002L, 004L and 010L standard pattern fittings are recommended to use.
- 10" and 12", Style 002L, 004L and 010L standard pattern fittings are recommended to use.
- Standard pattern fittings are used for Large Scale Fire Protection System in order to reduce the friction loss.
- For correct installation, please refer to page 91"General of Installation" and Publication AZ-100-EN "Installation Manual".
- For ONE TIME FIELD TEST ONLY, the Max. Joint working pressure may be increased to 1.5 times the figures shown.

LPC refer to page 13 for details.  
% JIS Standard



**VISION**  
A VISION COMPANY

VISION INTERNATIONAL | No.221 Jin Lan Rd.,JiaDing Industrial Park,Shanghai P.R. China,Tel:+86-21-5954-5863,Fax:+86-21-5954-3888

www.visionpiping.com

| FIRE PROTECTION SYSTEM | INTERNATIONAL |

NINGBO VISION PIPEFITTING CO.,LTD.,Xiaogang,Xinquan Village,Beilun District,Ningbo,Zhejiang P.R.of China ,Tel:+86-574-8615-6262